

Summary

Sensitivity and Schedule


T. Mori

Background and Sensitivity


	proposal	
δE_γ (%)	1.4 (2.0)	4.0–4.5
δp_e (%)	0.7	0.7–0.9
$\delta t_{e\gamma}$ (nsec)	0.15	0.15
· δt_e (nsec)	0.1	0.1
· δt_γ (nsec)	0.1	0.1
· δz_γ (mm)	16	16–18
$\delta\theta_{e\gamma}$ (mrad)	12 (14)	17–20.5
· $\delta\theta_e$ (mrad)	9	9–12
· δd_e (mm)	2.1	2.1–2.5
· δx_γ (mm)	4 (7)	9–10.5
$\Omega/4\pi$	0.09	0.09
ϵ_e	0.95	0.9
ϵ_γ	0.7	0.6
ϵ_{sel}	0.8	0.7
R_μ /sec	1.0×10^8	$(0.2–0.3) \times 10^8$
T sec	2×10^7	2.6×10^7
S_{1ev}	0.94×10^{-14}	$(3.8–5.6) \times 10^{-14}$
B_{acc}	0.5×10^{-14}	$(2.2–3.5) \times 10^{-14}$
N_{acc}	0.5	0.6
S_{90}	2.9×10^{-14}	$(1.0–1.6) \times 10^{-13}$

14

17 - 28 times worse sensitivity, 30% poorer acceptance




Constant	6693.
Mean	2.617
Sigma	0.6092



We anticipate further improvements in the detector performance:





- absorption length of 100cm assumed
- present PMTs assumed
- no elaborate optimization of detector configuration has been made
- reconstruction methods are not sophisticated enough

Absorption length of 100cm achieved







EVENT 8
TYPE 1




Simulation of the Photon Detector







MC Energy Resolution




	proposal	
δE_γ (%)	1.4 (2.0)	4.0–4.5
δp_e (%)	0.7	0.7–0.9
$\delta t_{e\gamma}$ (nsec)	0.15	0.15
· δt_e (nsec)	0.1	0.1
· δt_γ (nsec)	0.1	0.1
· δz_γ (mm)	16	16–18
$\delta\theta_{e\gamma}$ (mrad)	12 (14)	17–20.5
· $\delta\theta_e$ (mrad)	9	9–12
· δd_e (mm)	2.1	2.1–2.5
· δx_γ (mm)	4 (7)	9–10.5
$\Omega/4\pi$	0.09	0.09
ϵ_e	0.95	0.9
ϵ_γ	0.7	0.6
ϵ_{sel}	0.8	0.7
R_μ /sec	1.0×10^8	$(0.2–0.3) \times 10^8$
T sec	2×10^7	2.6×10^7
S_{1ev}	0.94×10^{-14}	$(3.8–5.6) \times 10^{-14}$
B_{acc}	0.5×10^{-14}	$(2.2–3.5) \times 10^{-14}$
N_{acc}	0.5	0.6
S_{90}	2.9×10^{-14}	$(1.0–1.6) \times 10^{-13}$







(a)



(b)




(c)





(d)

	proposal	
δE_γ (%)	1.4 (2.0)	4.0–4.5
δp_e (%)	0.7	0.7–0.9
$\delta t_{e\gamma}$ (nsec)	0.15	0.15
· δt_e (nsec)	0.1	0.1
· δt_γ (nsec)	0.1	0.1
· δz_γ (mm)	16	16–18
$\delta\theta_{e\gamma}$ (mrad)	12 (14)	17–20.5
· $\delta\theta_e$ (mrad)	9	9–12
· δd_e (mm)	2.1	2.1–2.5
· δx_γ (mm)	4 (7)	9–10.5
$\Omega/4\pi$	0.09	0.09
ϵ_e	0.95	0.9
ϵ_γ	0.7	0.6
ϵ_{sel}	0.8	0.7
R_μ /sec	1.0×10^8	$(0.2–0.3) \times 10^8$
T sec	2×10^7	2.6×10^7
S_{1ev}	0.94×10^{-14}	$(3.8–5.6) \times 10^{-14}$
B_{acc}	0.5×10^{-14}	$(2.2–3.5) \times 10^{-14}$
N_{acc}	0.5	0.6
S_{90}	2.9×10^{-14}	$(1.0–1.6) \times 10^{-13}$

Small Prototype Tests



Conversion Point Resolutior




	proposal	
δE_γ (%)	1.4 (2.0)	4.0–4.5
δp_e (%)	0.7	0.7–0.9
$\delta t_{e\gamma}$ (nsec)	0.15	0.15
· δt_e (nsec)	0.1	0.1
· δt_γ (nsec)	0.1	0.1
· δz_γ (mm)	16	16–18
$\delta\theta_{e\gamma}$ (mrad)	12 (14)	17–20.5
· $\delta\theta_e$ (mrad)	9	9–12
· δd_e (mm)	2.1	2.1–2.5
· δx_γ (mm)	4 (7)	9–10.5
$\Omega/4\pi$	0.09	0.09
ϵ_e	0.95	0.9
ϵ_γ	0.7	0.6
ϵ_{sel}	0.8	0.7
R_μ /sec	1.0×10^8	$(0.2–0.3) \times 10^8$
T sec	2×10^7	2.6×10^7
S_{1ev}	0.94×10^{-14}	$(3.8–5.6) \times 10^{-14}$
B_{acc}	0.5×10^{-14}	$(2.2–3.5) \times 10^{-14}$
N_{acc}	0.5	0.6
S_{90}	2.9×10^{-14}	$(1.0–1.6) \times 10^{-13}$

□ $E > 5$ MeV energy deposit on adjacent

□-cells to achieve 100 ps FWHM resolution


Resolution vs position



	proposal	
δE_γ (%)	1.4 (2.0)	4.0–4.5
δp_e (%)	0.7	0.7–0.9
$\delta t_{e\gamma}$ (nsec)	0.15	0.15
· δt_e (nsec)	0.1	0.1
· δt_γ (nsec)	0.1	0.1
· δz_γ (mm)	16	16–18
$\delta\theta_{e\gamma}$ (mrad)	12 (14)	17–20.5
· $\delta\theta_e$ (mrad)	9	9–12
· δd_e (mm)	2.1	2.1–2.5
· δx_γ (mm)	4 (7)	9–10.5
$\Omega/4\pi$	0.09	0.09
ϵ_e	0.95	0.9
ϵ_γ	0.7	0.6
ϵ_{sel}	0.8	0.7
R_μ /sec	1.0×10^8	$(0.2–0.3) \times 10^8$
T sec	2×10^7	2.6×10^7
S_{1ev}	0.94×10^{-14}	$(3.8–5.6) \times 10^{-14}$
B_{acc}	0.5×10^{-14}	$(2.2–3.5) \times 10^{-14}$
N_{acc}	0.5	0.6
S_{90}	2.9×10^{-14}	$(1.0–1.6) \times 10^{-13}$

$$\epsilon(\epsilon) = 60\%$$

Detector		Radiation thickness X_0
Magnet	Coil	0.153
	Cryostat	0.048
Photon Detector	Outer wall	0.03
	Honeycomb	0.068
	PMT+holder	0.21
Total		0.482



$\epsilon(\text{reconstruction}) = ? \%$


$$\epsilon(e^+) = 90\%$$

$$\epsilon(\text{trig}) > 97\%$$

$$\epsilon(100\text{ps}) = 94\%$$

$$\epsilon(140\text{ps}) = 99\%$$

$$\epsilon(\text{tracking}) = ?\%$$



	proposal	
δE_γ (%)	1.4 (2.0)	4.0–4.5
δp_e (%)	0.7	0.7–0.9
$\delta t_{e\gamma}$ (nsec)	0.15	0.15
· δt_e (nsec)	0.1	0.1
· δt_γ (nsec)	0.1	0.1
· δz_γ (mm)	16	16–18
$\delta\theta_{e\gamma}$ (mrad)	12 (14)	17–20.5
· $\delta\theta_e$ (mrad)	9	9–12
· δd_e (mm)	2.1	2.1–2.5
· δx_γ (mm)	4 (7)	9–10.5
$\Omega/4\pi$	0.09	0.09
ϵ_e	0.95	0.9
ϵ_γ	0.7	0.6
ϵ_{sel}	0.8	0.7
R_μ /sec	1.0×10^8	$(0.2–0.3) \times 10^8$
T sec	2×10^7	2.6×10^7
S_{1ev}	0.94×10^{-14}	$(3.8–5.6) \times 10^{-14}$
B_{acc}	0.5×10^{-14}	$(2.2–3.5) \times 10^{-14}$
N_{acc}	0.5	0.6
S_{90}	2.9×10^{-14}	$(1.0–1.6) \times 10^{-13}$

	proposal	
δE_γ (%)	1.4 (2.0)	4.0–4.5
δp_e (%)	0.7	0.7–0.9
$\delta t_{e\gamma}$ (nsec)	0.15	0.15
· δt_e (nsec)	0.1	0.1
· δt_γ (nsec)	0.1	0.1
· δz_γ (mm)	16	16–18
$\delta\theta_{e\gamma}$ (mrad)	12 (14)	17–20.5
· $\delta\theta_e$ (mrad)	9	9–12
· δd_e (mm)	2.1	2.1–2.5
· δx_γ (mm)	4 (7)	9–10.5
$\Omega/4\pi$	0.09	0.09
ϵ_e	0.95	0.9
ϵ_γ	0.7	0.6
ϵ_{sel}	0.8	0.7
R_μ /sec	1.0×10^8	$(0.2–0.3) \times 10^8$
T sec	2×10^7	2.6×10^7
S_{1ev}	0.94×10^{-14}	$(3.8–5.6) \times 10^{-14}$
B_{acc}	0.5×10^{-14}	$(2.2–3.5) \times 10^{-14}$
N_{acc}	0.5	0.6
S_{90}	2.9×10^{-14}	$(1.0–1.6) \times 10^{-13}$

Schedule

Obtain the Result (Discovery or Limit):

Before the **LHC** Experiments (>2007)


and

Before the **MECO** Experiment
(still waiting to be funded)

We foresee:

- Start beam tuning with the COBRA toward the end of 2003
- Engineering runs to start in 2004

Depends on budget approval



Requests to PSI

Understanding a new postdoc will be appointed to work on the DC this fall, we request the PSI:

- to support at least 2 students from outside institutes to stay at PSI, and
- to secure a budget of order of \$1.3M so that the collaboration can proceed and complete the construction of the detectors in a timely fashion.

Conclusion